

aval Research Laboratory

Ishington, DC 20375-5000

NRL Memorandum Report 6595

Measurement of Plasma-Neutralized Super-Vacuum Currents in a Gyrotron Configuration

D. A. KIRKPATRICK*, S. H. GOLD, W.M. MANHEIMER, W.M. BLACK, A.K. KINKEAD, D. L. HARDESTY, K. W. KILLIAN, AND M. SUCY**

Beam Physics Branch Plasma Physics Division

*Science Applications International Corporation McLean, VA 22102

> **JAYCOR, Inc. Vienna, VA 22180

February 16, 1990



Approved for public release; distribution unlimited.

SECURITY CLASSIFICATION OF THIS PAGE							
			REPORT DOCUM	MENTATION	PAGE		
1a. REPORT SECURITY CLASSIFICATION Unclassified			1b. RESTRICTIVE MARKINGS				
2a. SECURITY C	LASSIFICATION	VAUTHORITY		3 DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution unlimited.			
2b. DECLASSIFIC	ATION / DOW	NGRADING SCHEDU	LE				
4. PERFORMING	ORGANIZATI	ON REPORT NUMBER	R(S)	5. MONITORING	ORGANIZATION RE	PORT NU	MBER(S)
NRL Memor	andum Re	port 6595					
6a. NAME OF P	ERFORMING (ORGANIZATION	6b. OFFICE SYMBOL	7a. NAME OF M	ONITORING ORGAN	NIZATION	
Naval Research Laboratory (If applicable) Code 4793							
6c. ADDRESS (C				7b. ADDRESS (City, State, and ZIP Code)			
Naval Res Washingto							
8a. NAME OF F		NSORING	8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER			
Office of	Naval Re	esearch		47-2797-0-0			
8c. ADDRESS (Ci	ty, State, and	ZIP Code)		10. SOURCE OF	FUNDING NUMBER	\$	
ONR		217		PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.	WORK UNIT ACCESSION NO.
Arlington	l, VA 22.	217				RR011-	
11. TITLE (Inclue	-	·			·· ······················		
Measureme	ent of Pla	asma-Neutrali	zed Super-Vacuum	Currents i	n a Gyrotron	Confi	guration
12. PERSONAL			D.A.*, Gold, S.H , Hardesty, D.L.				
13a. TYPE OF R		13b. TIME CO			ORT (Year, Month, L		PAGE COUNT
Memorandum FROM 2/88 TO 9/89			1990 Febr	uary 16	L_	20	
16. SUPPLEMEN			ional Commonatio	m Matann	*** 22102		
			ional Corporatio 180	on, McLean,	VA 22102		
17	COSATI		18. SUBJECT TERMS (C	ontinue on revers	e if necessary and	identify l	by block number)
FIELD	GROUP	SUB-GROUP	5 Super+Vacuum	Currents; P	lasma Neutra	lizati	on; Gyrotron,
			,				_
19 ARSTRACT /	Continue on	reverse if peressan	and identify by block n	umber)			
			ted on the trans		electron bea	m with	current in
			rge limited valu				
gyrotron	oscillato	ors. The vac	uum space-charge	limit is c	ircumvented	by the	introduction
			lasma which is p		an array of	four p	lasma guns
		y downstream	of the electron	gun anode.			
Hero .	12						
·							
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT			21. ABSTRACT SECURITY CLASSIFICATION				
Za unclassified/unlimited			Unclassi	fied (Include Area Code)	1226 05	FICE SYMBOL	
S.H. Gold			(202) 767-		1	= 4793	

CONTENTS

INTRODUCTION	1
ACKNOWLEDGMENT	5
REFERENCES	6
DISTRIBUTION LIST	9

Access	ion For	
NTIS DTIC 1 Unanno Justii	rab 🚹	
	ibution/	
1	larility Codes	(III)
Dist	Avgil and/or Special	
A-1		

Measurement of Plasma-Neutralized Super-Vacuum Currents in a Gyrotron Configuration

A high power microwave device typically consists of an intense relativistic electron beam driving a beam-wave interaction in an evacuated cavity or interaction volume. This includes slow-wave devices such as backward-wave oscillators (BWO)^{1,2} and relativistic klystrons, and fast-wave devices such as gyrotrons^{3,4} and free-electron lasers^{5,6}. A fundamental limit to the power of such devices can be obtained by multiplying their theoretical interaction efficiency by the maximum beam power that can be propagated. For a particular voltage and geometry, the maximum beam power is set by the vacuum limiting current. This limit on the beam current arises from the fact that the electron beam loses an amount of energy corresponding to the capacitive voltage drop between the electron beam and the conducting boundary.

Recently there has been much interest in exceeding the space-charge limit in high power microwave devices, notably the gyrotron and BWO^{7,8,9}. The space-charge limit is severe in the gyrotron due to the nature of the gyrotron interaction, which is more favorable when the beam α is large ($\alpha = \beta_{\perp}/\beta_{\parallel}$, the ratio of perpendicular to parallel velocities). The space-charge limiting current for a cold annular beam of vanishing thickness is given by¹⁰

$$I_{L0} = I_A \frac{\gamma_0 \left[1 - (1 - \beta_{z0}^2)^{1/3} \right]^{3/2}}{2 \ln(R_w/R_{beam})} \tag{1}$$

where I_A is the Alfven current (17.07 kA), $\gamma_0 = 1 + (eV_0/m_0c^2)$ is the relativistic factor associated with the electron energy in the absence of any space-charge depression, $\beta_{z0} = v_{z0}/c$, v_{z0} is the electron axial velocity prior to any space-charge depression, R_w is the radius of the conducting boundary, and R_{beam} is the radius of the electron beam. The large beam α which is desirable for operation of the gyrotron corresponds to low β_{z0} , and therefore low limiting currents.

One possible means to circumvent this obstacle is to use a neutral background plasma to short out the self-electric field of the electron beam. This concept of a neutralizing Manuscript approved December 20, 1989.

background plasma has been investigated extensively in the Soviet Union⁷, and has recently been the focus of some investigations with regard to the BWO⁹. In order for the background plasma to cancel the effects of the electron beam self-electric field, the density of the neutral plasma must be greater than the density of the beam electrons, so that sufficient background electrons may be expelled from the region of the transiting electron beam to provide for space-charge neutralization.

In this paper we report on the achievement of super-vacuum currents (beam currents in excess of the vacuum space-charge limit) in a configuration directly applicable to gyrotron oscillators. The experimental arrangement is shown in Fig. 1. The VEBA pulseline accelerator ($V \sim 0.6 - 2.5 \,\mathrm{MV}, \, I \sim 20 - 100 \,\mathrm{kA}, \, \tau \sim 60 \,\mathrm{ns}$) is used to energize an electron gun which produces an annular electron beam. The electron gun consists of a hollow cylindrical cathode and an anode mask with an annular aperture. Both the cathode and the anode are fabricated from reactor-grade graphite. The annulus in the anode mask has an inner radius of 1.6 cm and and outer radius of 1.9 cm. The cathode-anode gap is 2.1 cm. Directly downstream from the anode mask is a Rogowski coil which measures the emitted beam current on each accelerator pulse. Immediately following is an array of four plasma guns¹¹, equally spaced in azimuth. The plasma guns are individually energized by an array of four 0.22 µF capacitors which are typically charged to 14 kV. The entire system is immersed in a uniform 10 kG axial guide magnetic field, produced by an external solenoid. In addition, as shown in Fig. 1, there is a field reversed, thin-solenoid "dip" magnet which is used to spin up the electron beam¹², and a Helmholtz pair positioned symmetrically about the cavity region. In these experiments the cavity region is composed of a simple straight wall drift space. The magnetic field in the center of the cavity region is 29 kG.

The plasma density produced in the cavity region has been characterized by 70 GHz quadrature microwave interferometry and by time-integrated photography of the light emitted by the plasma. The photographs of the light emitted by the plasma in the cavity region indicate that while the plasma is relatively uniform in the azimuthal direction, significant

non-uniformity exists in the radial direction, with the peak density being close to the cavity wall. Close inspection of the interferometry data shows the presence of cutoff-level densities early in the plasma pulse, when the line-averaged plasma density is computed to be about $10^{13} \, \mathrm{cm}^{-3}$. Since the plasma cutoff for our 70 GHz interferometer occurs at $n_p = 6 \times 10^{13} \, \mathrm{cm}^{-3}$, this would suggest peak densities on the order of a factor of five greater than the line averaged densities. The data presented here are obtained with line-averaged plasma densities in the range $1.5-5\times 10^{11} \, \mathrm{cm}^{-3}$, corresponding to peak background plasma densities in the range $0.8-3\times 10^{12} \, \mathrm{cm}^{-3}$.

The achievement of super-vacuum currents is demonstrated by measuring the beam current transported through the cavity region with and without the background neutralizing plasma, while varying the amplitude of the "dip" magnet. This data is shown in Fig. 2(a), where we plot the measured cavity current against the amplitude of the "dip" magnet for both the vacuum and plasma-neutralized cases. For the plasma-neutralized case the data represent the maximum measured signals across a sample of neutral plasma densities. This step is necessary because with too little plasma background the beam is not neutralized, while with too much plasma background the beam current is partially neutralized and the Rogowski measurement gives an artificially low account of the beam current. Similarly, as the "dip" magnitude increases the average beam axial velocity decreases, which results in an increase in the local number density of beam electrons. The higher number density of beam electrons requires a greater background plasma density to provide for neutralization. The variation of the plasma density is achieved by varying the time delay between the firing of the plasma guns and the firing of the accelerator. For our measured beam parameters, and using the estimated beam alpha, the peak number density of the beam electrons is in the range $1-3\times10^{12}\,\mathrm{cm}^{-3}$. Combined with our previous estimate of the relative nonuniformity of the neutral background plasma, the condition for neutralization of $n_b \approx n_p$ appears to be well met.

The variation of α with the amplitude of the dip magnet is shown in Fig. 2(b). Here

we plot the average and spread in α for the calculated trajectories of an ensemble of non-interacting particles, using the measured magnetic fields and electron beam voltage. The calculated transmitted current for these single particle ensembles is shown in Fig. 2(a) as the "mirror limiting current". In this case, the loss of current is due wholly to mirroring of individual particles in the region of the magnetic compression. It can be seen that there is good agreement between this curve and the measured data for the plasma neutralized case. Similarly, we can use the calculated beam alpha to calculate space-charge limiting current for a zero-temperature beam of non-zero thickness¹⁰, and the space-charge limiting current for a zero-thickness beam with a non-zero thermal spread in velocity¹³. These curves are shown in Fig. 2(a) as $I_{SC}(\Delta r)$ and $I_{SC}(\Delta \alpha)$, respectively. Both curves are seen to agree reasonably well with the measured data for the vacuum case. It should be noted that for pump amplitudes corresponding to an average beam α of 1 to 2, the presence of the neutralizing plasma results in an increase in the beam current propagated through the cavity by a factor of about three.

The calculations of $I_{SC}(\Delta r)$, $I_{SC}(\Delta \alpha)$, and the mirror limiting current shown in Fig. 2(a) are obtained using a very simple electron beam distribution function. The inner and outer radii of the electron beam correspond to the inner and outer radii of the anode mask aperture. The velocity distribution assumes a uniform spread in initial diode α ranging from 0 to 0.1. This range gave good agreement for both the roll-over point of the mirror limiting current, and for the space-charge limited current in the case of no pump field. Deviations of the theoretical curves from the data, for both the vacuum and plasma-neutralized cases, are probably due to the details the electron beam distribution function which are grossly simplified in the calculations. Further, no accounting has been made of the possibility of diamagnetic effects associated with the high- α beam, nor do the calculations consider the effect of space charge on the "spinning up" of the electron beam by the pump magnet.

In conclusion, we have demonstrated transport of beam currents in excess of the vacuum space-charge limit in a plasma-filled, gyrotron type cavity. For values of the beam alpha in

the range of 1 to 2 the increase in electron beam current is approximately a factor of three. Comparison of the measured transmitted vacuum current with the theoretical vacuum space-charge limited current shows good agreement. In the case of the plasma neutralized measurements, we obtain good agreement from a simple calculation of magnetic mirroring of an ensemble of non-interacting electrons, where the ensemble is taken to represent a uniform, low initial temperature, annular beam of radial dimensions given by the anode mask. The higher intra-cavity beam currents achieved with the aid of the neutralizing background plasma should enable higher power operation in existing intense beam gyrotron designs¹⁴.

Acknowledgments

The authors would like to acknowledge the assistance of B. Weber of NRL with the use of the plasma guns, setup of the microwave interferometry, and associated data analysis programs. This work was supported by the Office of Naval Research.

References

- ¹ Y. Carmel et al., Phys. Rev. Lett. 33, 1278 (1974).
- ² N. Kovalev *et al.*, Pis'ma Zh. Eksp. Teor. Fiz. **18**, 232 (1973) [JETP Lett. **18**, 138 (1973)].
- ³ V.L. Granatstein, Int. J. Electron. 57, 787 (1984).
- ⁴ S.P. Bugaev *et al.*, Pis'ma Zh. Tekh. Fiz. **9**, 1385 (1983) [Sov. Tech. Phys. Lett. **9**, 596 (1983)].
- ⁵ J. Fajans et al., Phys. Fluids 28, 1995 (1985).
- ⁶ T.J. Orzechowski et al., Phys. Rev. Lett. 54, 889 (1985).
- ⁷ M.V. Kuzelev *et al.*, Fiz. Plazmy **13**, 1370 (1987) [Sov. J. Plasma Phys. **13**, 793 (1987)].
- ⁸ V.I. Kurilko *et al.*, Zh. Tekh. Fiz. **51**, 1415 (1981) [Sov. Phys. Tech. Phys. **26**, 812 (1981)].
- ⁹ Y. Carmel et al., Phys. Rev. Lett. 62, 2389 (1989).
- ¹⁰ A.K. Ganguly and K.R. Chu, Int. J. Infrared Millimeter Waves 5, 103 (1984).
- ¹¹ R.J. Commisso et al., NRL Memo Report 6057, Naval Research Laboratory, Wash. DC 20375-5000 (1987).
- ¹² S.H. Gold et al., Phys. Fluids 30, 2226 (1987).
- ¹³ T. Antonsen and B. Levush, Int. J. Electron. **61**, 871 (1986)
- ¹⁴ W.M. Black et al., Phys. Fluids B 2, 193 (1990).




Fig. 1. The schematic layout of the VEBA plasma-neutralized gyrotron experiment, showing the magnet positions, inner conducting wall, vacuum chamber, microwave interferometry windows, plasma guns, and cathode-anode positions.




Fig. 2. The current measured by the Rogowski coil positioned in the cavity region, for the vacuum case (open circles) and for the plasma-neutralized case (solid circles), shown with the calculated vacuum space-charge limiting current for a beam of non-zero thickness (dotted line), the calculated vacuum space-charge limiting current for a beam with non-zero thermal spread (thin line), and the calculated transmitted current for an ensemble of non-interacting electrons (bold line).

4793/4 DISTRIBUTION LIST

Air Force Avionics Laboratory AFWAL/AADM-1 Wright/Patterson AFB, OH 45433 Attn: Walter Friez	1 copy
Air Force Office of Scientific Research Bolling AFB Washington, D.C. 20332 Attn: H. Schlossberg	1 copy
Air Force Weapons Lab Kirkland AFB Albuquerque, NM 87117 Attn: Dr. William Baker Dr. A.H. Guenter	2 copies 1 copy
Bhabha Atomic Research Center Laser Division Bombay, India 400085 Attn: T.S. Shirsat	1 сору
Columbia University 520 West 120th Street Department of Electrical Engineering New York, NY 10027 Attn: Dr. S.P. Schlesinger	1 copy
A. Sen Columbia University 520 West 120th Street Department of Applied Physics	1 copy
and Nuclear Engineering New York, NY 10027 Attn: T.C. Marshall R. Gross	1 copy 1 copy
Cornell University School of Applied and Engineering Physics Ithica, NY 14853 Attn: Prof. Hans H. Fleischmann John Nation	1 copy
R. N. Sudan Creol-FEL Research Pavillion 12424 Research Parkway, Suite 400	1 copy 1 copy
Orlando, FL 32826 Attn: Dr. Luis R. Elias Dr. I. Kimel	1 copy 1 copy

Dartmouth College 18 Wilder, Box 6127 Hanover, NH 03755 Dr. John E. Walsh 1 copy Defense Advanced Research Project Agency/DEO 1400 Wilson Blvd. Arlington, VA 22209 Attn: Dr. L. Buchanan 1 copy Defense Communications Agency Washington, D.C. 20305 Dr. Pravin C. Jain Assistant for Communications Technology 1 copy Defense Nuclear Agency Washington, D.C. 20305 Attn: Mr. J. Farber 1 copy Dr. Leon Wittwer (RAAE) 5 copies Defense Technical Information Center Cameron Station 5010 Duke Street Alexandria, VA 22314 2 copies Department of Energy Div. of Advanced Energy Projects Washington, DC 20545 Attn: Dr. R. Gajewski 1 copy Department of Energy Office of Energy Research Washington, D.C. 20545 C. Finfgeld/ER-542, GTN 1 copy Attn: 1 copy T.V. George/ER-531, GTN D. Crandall/ER-54, GTN 1 copy Dr. David F. Sutter/ER-224, GTN 1 copy Director of Research U. S. Naval Academy Annapolis, MD 21402-5021 1 copy General Atomics 13-260 Box 85608 San Diego, CA 92138 ATTN: Dr. J. Doane 1 copy 1 copy Dr. C. Moeller

Georgia Tech. EES-EOD Baker Building Atlanta, GA 30332	
Attn: Dr. James J. Gallagher	1 copy
Hanscomb Air Force Base Stop 21, MA 01731	
Attn: Lt. Rich Nielson/ESD/INK	1 copy
Hughes Aircraft Co.	
Electron Dynamics Division 3100 West Lomita Boulevard	
Torrance, CA 90509	
Attn: J. Christiansen	1 copy
J. Tancredi	1 copy
Hughes Research Laboratory	
3011 Malibu Canyon Road	
Malibu, CA 90265	•
Attn: Dr. R. Harvey Dr. R.W. Schumacher	1 copy
DI. R.W. Schumacher	1 copy
KMS Fusion, Inc.	
3941 Research Park Dr.	
P.O. Box 1567	
Ann Arbor, MI 48106	1
Attn: S.B. Segall	1 copy
Lawrence Berkeley Laboratory	
University of California	
1 Cyclotron road	
Berkeley, CA 94720 Attn: Dr. A.M. Sessler	1 conv
Attn: DI. A.M. Sessiel	1 copy
Lawrence Livermore National Laboratory P.O. Box 808	
Livermore, CA 94550	
Attn: Dr. D. Prosnitz	1 copy
Dr. T.J. Orzechowski	1 copy
Dr. J. Chase	1 copy
Dr. W.A. Barletta	1 copy
Dr. D.L. Birx	1 copy
Dr. E.T. Scharlemann	1 copy
Litton Electron Devices	
960 Industrial Road	
San Carlos, CA 94070	
Attn: Library	1 copy

```
Los Alamos National Scientific Laboratrov
P.O. Box 1663, MSJ 564
Los Alamos, NM 87545
      Dr. Brian Newman
Attn:
                                                   1 copy
Los Alamos Scientific Laboratory
P.O. Box 1663, AT5-827
Los Alamos, NM 87545
        Dr. T.J.T. Kwan
Attn:
                                                   1 copy
        Dr. L. Thode
                                                   1 copy
        Dr. R. R. Bartsch
                                                   1 copy
Massachusetts Institute of Technology
Department of Physics
Cambridge, MA 02139
        Dr. G. Bekefi/36-213
Attn:
                                                   1 copy
        Dr. M. Porkolab/NW 36-213
                                                   1 copy
        Dr. R. Davidson/NW 16-206
                                                   1 copy
        Dr. A. Bers/NW 38-260
                                                   1 copy
        Dr. K. Kreischer
                                                   1 copy
        Dr. B. Danby
                                                   1 copy
        Dr. G.L. Johnston
                                                   1 copy
Massachusetts Institute of Technology
167 Albany St., N.W. 16-200
Cambridge, MA 02139
       Dr. R. Temkin/NW 14-4107
                                                   1 copy
Mission Research Corporation
8560 Cinderbed Road, Suite 700
Newington, VA 22122
      Dr. M. Bollen
Attn:
                                                   1 copy
        Dr. Tom Hargreaves
                                                   1 copy
        Dr. J. Pasour
                                                   1 copy
Naval Research Laboratory
Addressee: Attn: Name/Code
Code 0124 - ONR
                                                   1 copy
Code 1000 - Commanding Officer
                                                   1 copy
Code 1001 - T. Coffey
                                                   1 copy
Code 1003.9A - Computer Resources Architect
                                                   1 copy
Code 1005 - Head, Office of Mgt. & Admin.
                                                   1 copy
Code 1005.1 - Deputy Head, Off. of Mgt. & Admin. 1 copy
Code 1005.6 - Head, Directives Staff
                                                   1 copy
Code 1200 - Capt. R.W. Michaux
                                                   1 copy
Code 1201 - Deputy Head, Command Support Division 1 copy
Code 1220 - Security
                                                   1 copy
Code 2000 - J. Brown
                                                   1 copy
Code 2604 - NRL Historian
                                                   1 copy
Code 2628 - TID Distribution
                                                  22 copies
Code 2634 - Cindy Sims
                                                   1 copy
Code 3000 - R. Doak
                                                   1 copy
```

Code 4000 - W. Ellis Code 4000 - D. Nagel Code 4700 - S. Ossakow Code 4700.1 - A. Ali Code 4790 - Branch Office Code 4790 - W. Black Code 4790 - G. Cooperstein Code 4790 - A. Fliflet Code 4790 - S. Gold Code 4790 - C. Hui Code 4790 - C. Kapetanakos Code 4790 - A. Kinkead Code 4790 - Y. Lau Code 4790 - W. Manheimer Code 4790 - W. Manheimer Code 4790 - M. Rhinewine Code 4790 - P. Sprangle Code 5700 - L. Cosby Code 6840 - S. Abn	1 copy 1 copy 26 copies 1 copy 25 copies 1 copy
Code 6840 - S. Ahn Code 6840 - A. Ganguly Code 6840 - R. Parker Code 6840 - N. Vanderplaats Code 6850 - L. Whicker Code 6875 - R. Wagner	1 copy 1 copy 1 copy 1 copy 1 copy 1 copy
Naval Sea Systems Command Department of the Navy Washington, D.C. 20362 Attn: Commander, PMS 405-300 Northrop Corporation	1 copy
Defense Systems Division 600 Hicks Rd. Rolling Meadows, IL 60008 Attn: Dr. Gunter Dohler Oak Ridge National Laboratory	1 copy
P.O. Box Y Mail Stop 3 Building 9201-2 Oak Ridge, TN 37830 Attn: Dr. A. England	l copy
Office of Naval Research 800 N. Quincy Street Arlington, VA 22217 Attn: Dr. C. Roberson	l copy
Office of Naval Research 1012 W 36th Street, Childs Way Bldg. Los Angeles, CA 90089-1022 Attn: Dr. R. Behringer	l Copy

Optical Sciences Center	
University of Arizona	
Tucson, AZ 85721	
Attn: Dr. Willis E. Lamb, Jr.	1 copy
Physical Science Inc.	
603 King Street	
Alexandria, VA 22314	
ATTN: M. Read	1
AIIN. M. REAG	1 copy
Physics International	
2700 Merced Street	
San Leandro, CA 94577	
Attn: Dr. J. Benford	1 copy
Princeton Plasma	
Plasma Physics Laboratory	
James Forrestal Campus	
P.O. Box 451	
Princeton, NJ 08544	
Attn: Dr. H. Hsuan	2 copies
Dr. D. Ignat	1 copy
Dr. H. Furth	1 copy
Dr. P. Efthimion	1 copy
Dr. F. Perkins	1 copy
Bauthoon Company	
Raytheon Company Microwave Power Tube Division	
Foundry Avenue	
Waltham, MA 02154	
Attn: N. Dionne	1 copy
	_ 00P1
Sandia National Laboratories	
ORG. 1231, P.O. Box 5800	
Albuquerque, NM 87185	
Attn: Dr. Thomas P. Wright	1 copy
Mr. J.E. Powell	1 copy
Dr. J. Hoffman	1 copy
Dr. W.P. Ballard	1 copy
Dr. C. Clark	1 copy
Science Applications, Inc.	
1710 Goodridge Dr.	
McLean, VA 22102	
Attn: Adam Drobot	1 copy
P. Vitello	1 copy
D. Bacon	1 copy
C. Menyuk	1 copy
Science Research Laboratory	
15 Ward Street	
Somerville, MA 02143	
Attn: Dr. R. Shefer	1 copy
	- 20bl

SPAWAR Washington, D.C. 20363 Attn: E. Warden, Code PDE 106-3113 Capt. Fontana, PMW 145	1 copy 1 copy
Spectra Technologies 2755 Northup Way Bellevue, WA 98004 Attn: Dr. J.M. Slater	1 copy
Stanford University Dept. of Electrical Engineering Stanford, CA 94305 Attn: Dr. J. Feinstein	1 copy
Stanford University High Energy Physics Laboratory Stanford, CA 94305 Attn: Dr. T.I. Smith	1 copy
Stanford University SLAC Stanford, CA 94305 Attn: Dr. Jean Labacqz	1 copy
TRW, Inc. One Space Park Redondo Beach, CA 90278 Attn: Dr. H. Boehmer Dr. T. Romisser Dr. Z. Guiragossian	1 copy 1 copy 1 copy
University of California Physics Department Irvine, CA 92717 Attn: Dr. G. Benford Dr. N. Rostoker	1 copy 1 copy
University of California Department of Physics Los Angeles, CA 90024 Attn: Dr. A.T. Lin Dr. N. Luhmann	1 copy 1 copy
Dr. D. McDermott University of Maryland Department of Electrical Engineering College Park, MD 20742	1 copy
Attn: Dr. V. L. Granatstein Dr. W. W. Destler	1 copy 1 copy

University of Maryland Laboratory for Plasma and Fusion	
Energy Studies	
College Park, MD 20742	1
Attn: Dr. Tom Antonsen Dr. John Finn	1 copy 1 copy
Dr. Jhan Varyan Hellman	1 copy
Dr. W. Lawson	1 copy
Dr. Baruch Levush	1 copy
Dr. Edward Ott	1 copy
Dr. M. Reiser	1 copy
University of New Mexico	
Department of Physics and Astronomy	
800 Yale Blvd, N.E.	
Albuquerque, NM 87131 Attn: Dr. Gerald T. Moore	1 conv
	1 copy
University of Tennessee	
Dept. of Electrical Engr.	
Knoxville, TN 37916 Attn: Dr. I. Alexeff	1
Actn: Dr. 1. Alexell	1 copy
University of Utah	
Department of Electrical Engineering	
3053 Merrill Engineering Bldg.	
Salt Lake City, UT 84112 Attn: Dr. Larry Barnett	1 copy
Dr. J. Mark Baird	1 copy
U. S. Army	
Harry Diamond Labs	
2800 Powder Mill Road	
Adelphi, MD 20783-1145	•
Attn: Dr. Howard Brandt Dr. Edward Brown	1 copy
Dr. Stuart Graybill	1 copy 1 copy
Dr. A. Kehs	1 copy
Dr. J. Silverstein	1 copy
Varian Associates	
611 Hansen Way	
Palo Alto, CA 94303	•
Attn: Dr. H. Huey	1 copy
Dr. H. Jory Dr. Kevin Felch	1 copy
Dr. R. Pendleton	1 copy 1 copy
Dr. A. Salop	1 copy
•	7 0051
Varian Eimac San Carlos Division	
301 Industrial Way San Carlos, CA 94070	
Attn: C. Marshall Loring	1 copy
ut macumaa autamy	r coby

WL/CA Kirtland AFB, NM 87117-6008 Attn: Mr. Brendan B. Godfrey

1 copy

Yale University
Applied Physics
Madison Lab
P.O. Box 2159
Yale Station
New Haven, CN 06520
Attn: Dr. I. Bernstein

1 copy

Ken Busby

1 copy